



























































































AWUKO Qualities

Name	Characteristics	Grain No.					Areas of Applications		
KP12F antistatic	F-paper, very open coated, aluminium oxide, resin bond	P150-P60	✓		✓				✓
KP52F antistatic	F-paper, semi open coated, aluminium oxide, resin bond	P220-P60, P40	✓		✓				✓
KP80E	E-paper, dense coated, aluminium oxide, resin bond	P800-P36, P24	✓	✓	✓	✓	   	✓	✓
KP80E velcro	our AWUKO KP80E with velcro backing	P150-P36, P24		✓		✓	  	✓	✓
KP80E PSA	our AWUKO KP80E in PSA execution	P500, P400, P240-P40		✓		✓	  	✓	✓
KP81E	E-paper, special coating, aluminium oxide	600, 400-120			✓				✓
KP32C	flexible C-Latex paper, semi open coated, aluminium oxide, resin bond	P180-P80		✓	✓		 	✓	✓
KP32C velcro	our AWUKO KP32C with velcro backing	P180-P100		✓		✓	 	✓	✓
KP43E	E-paper, dense coated, aluminium oxide, hide glue	P1500-P100	✓		✓		 		✓
KP20F	F-paper, special coating, aluminium oxide, resin bond	P400, P320-P180	✓		✓				✓
ZP88F inox express	F-paper, dense coated, zircon corundum, resin bond	220-100	✓						✓
KP88F inox express	F-paper, dense coated, aluminium oxide, resin bond	P400, P320-P240	✓						✓
KP63D painter express	D-paper, special wave-form coating, hide glue	P180, P120-P60		✓	✓			✓	✓
KP73A	A-paper, semi open coated, aluminium oxide, hide glue	P1000, P800, P600, P400, P320-P60		✓	✓		 	✓	✓
KP73C	C-paper, semi open coated, aluminium oxide, hide glue	P400, P320, P240-P180, P120	✓	✓	✓		 	✓	✓
SP14A	A-paper, special stearate coating, silicon carbide, hide glue	P400, P320-P180		✓	✓		 	✓	✓
SP14A velcro	our AWUKO SP14A with velcro backing	P240, P220		✓	✓	✓	 	✓	✓
SP23B	B-paper, dense coated, silicon carbide, hide glue	P600-P180	✓	✓	✓			✓	✓
SP23E	E-paper, dense coated, silicon carbide, hide glue	P800-P150	✓	✓	✓			✓	✓
SP40E antistatic	E-paper, dense coated, silicon carbide, resin bond	P600-P240	✓	✓	✓	✓	  	✓	✓
SP40F antistatic	F-paper, dense coated, silicon carbide, resin bond	P400, P320-P36, P24	✓	✓	✓	✓	  	✓	✓
SP48G panel express	G-paper, dense coated, silicon carbide, resin bond	P220-P60	✓						✓



AWUKO ABRASIVES Wandmacher GmbH & Co. KG

Name	Characteristics	Grain No.					Areas of Applications		
SR40A	waterproofed A-paper, silicon carbide, resin bond	P1200, P1000, P800-P220		✓				✓	
SR40C	waterproofed C-paper, silicon carbide, resin bond	P180-P60		✓				✓	
KT62XF	x flex cotton cloth, close coated, aluminium oxide, resin bond	P400, P320, P240-P40	✓	✓	✓		  	✓	✓
KT62X	heavy cotton cloth, dense coated, aluminium oxide, resin bond	P180-P36, P24, P16	✓	✓	✓	✓	   	✓	✓
KT82X	X-flex cotton cloth, dense coated, aluminium oxide, resin bond	P120-P36, P24, P16	✓		✓	✓	 	✓	✓
KT62J	medium-soft cotton cloth, dense coated, aluminium oxide, resin bond	P240-P60	✓	✓	✓		 	✓	✓
KT62F	high-flexible cotton cloth, dense coated, aluminium oxide, resin bond	P800-P60	✓	✓	✓		 	✓	✓
KT20F	soft cotton cloth, dense coated, aluminium oxide, resin bond	P400, P320, P240, P180-P60, P40		✓	✓		 	✓	
ZT62X	heavy cotton cloth, dense coated, zircon corundum, resin bond	120-60, 40, 36, 24	✓		✓	✓	  		✓
ZT62X velcro	heavy cotton cloth, dense coated, zircon corundum, resin bond, velcro backing	120-60, 40, 36, 24				✓	 		✓
ZU62SY	heavy polyester cloth, dense coated, zircon corundum, resin bond, also for segmented belts	100-36, 24	✓		✓		 		✓
KU22SY panel express	extremely heavy polyester cloth, dense coated, aluminium oxide, resin bond, also for segmented belts	P150-P60, P40	✓		✓		 		✓
KW22X	heavy waterproofed cotton cloth, dense coated, aluminium oxide, resin bond	P600, P400, P240, P180	✓		✓				✓
SU22SY panel express	extremely heavy polyester cloth, dense coated, silicon carbide, resin bond, also for segmented belts	P180-P36, P24, P16	✓						✓
SU42Y	heavy polyester cloth, dense coated, silicon carbide, resin bond	P150-P36, P24	✓		✓	✓	  		✓
SW22X	heavy waterproofed cotton cloth, dense coated, silicon carbide, resin bond	P400, P320, P240, P220, P150	✓		✓		 		✓
ST10X	heavy cotton cloth, open coated, silicon carbide, resin bond	P16, P12	✓			✓	 		✓
KN22T	vulcanized fibre, dense coated, aluminium oxide, resin bond	P320-P24, P16				✓			✓
ZN22T	vulcanized fibre, dense coated, zircon corundum, resin bond	P120-P24, P16				✓			✓
































AWUKO ABRASIVES Wandmacher GmbH & Co. KG

Hedemündener Straße 9
D-34346 Hann. Münden

E-Mail: info@awuko.de
Website: <http://www.awuko.com>

Telephon: +49 (0)5541 7097-0
Fax national: 05541 6727
Fax international: +49 (0) 5541 6729

AWUKO ABRASIVES Wandmacher GmbH & Co. KG

Name	Characteristics	Grain No.					Areas of Applications		
OK96L	polishing combination, cotton fabric on sodium kraft paper	-	✓		✓				✓
KP85F	F-Paper, close coated, aluminium oxide, resin bond	P80,P60	✓						✓
Sponges hard	foam sponge, 4-side-coated, aluminium oxide	220-60					 	✓	
Sponges flexible	soft foam sponge, coated on 4 sides, aluminium oxide	180, 120, 100					 	✓	
Mats black	soft, flexible foam material, coated on 2 sides, silicon carbide	220-100, 60					 	✓	
Mats white	high flexible foam mat, coated on 1-side	100					 	✓	
Fleece A	nylon fibre fleece, aluminium oxide, resin bond	A1000, A400, A280, A180, A100		✓	✓	✓	 	✓	✓
Fleece S	nylon fibre fleece, silicon carbide, resin bond	S1000+ S400		✓	✓	✓	 	✓	✓
Sanding Screen	sanding screen, silicon carbide, resin bond	220-60				✓	  		✓
Floor Sanding Pads	available in colour: black, green, red, beige and white (thin: 10mm / thick: 20mm)	-				✓			✓
Graphite Cloth	graphite cloth available in execution HD	-		✓	✓				✓
KP16C velcro	flexible C-latex paper with velcro, semi-open coated, aluminium oxide, resin bond with stearate coating	P600, P400, P320, P240-P60, P40		✓		✓	 	✓	✓
KP16C	flexible C-latex paper, semi-open coated, aluminium oxide, resin bond with stearate coating	P1000, P800, P400, P320,P240	✓	✓	✓		 	✓	✓
SOFT	flexible A-latex paper on foam, semi-open coated, aluminium oxide, resin bond with stearate coating	P400, P320-P150			✓		 	✓	
GU65Y	waterproof polyester, dense coated, SG-ceramics, resin with grinding active additives	120-36, 24	✓		✓				✓

